NSN 5905-00-144-8431

Section Quantity:

Cylindrical bushing mounted

Body Style:

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-144-8431

First Flat Length:
0.343 inches
Flat Height:
0.218 inches
Body Diameter:
1.562 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.875 inches
Mounting Bushing Length:
0.375 inches
Body Length:
1.375 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.500 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
Electrical Resistance I of Occiton.
6.000 ohms single section
6.000 ohms single section
6.000 ohms single section Power Dissipation Rating Per Section In Watts:
6.000 ohms single section Power Dissipation Rating Per Section In Watts: 25.0 free air single section
6.000 ohms single section Power Dissipation Rating Per Section In Watts: 25.0 free air single section Resistance Tolerance Per Section In Percent:

NSN 5905-00-144-8431

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0