## NSN 5905-00-145-3690

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-145-3690 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Overall Length:** 0.415 inches **Terminal Length:** 0.172 inches **Overall Height:** 0.375 inches **Overall Width:** 0.333 inches **Body Length:** 0.375 inches **Body Width:** 0.161 inches **Body Height:** 0.375 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Maximum Starting Torque:** 5.00 inch-ounces **Center To Center Distance Between Terminals:** 0.200 inches **Fragility Factor:** Moderately delicate **Terminal Location:** Right adjacent side single row **Mounting Method: Terminal Features Provided:** Humidity proof **Electrical Resistance Per Section:** 1.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 9000.0

**Center To Center Distance Between Center Terminal And Outside Terminal:** 

0.100 inches

## NSN 5905-00-145-3690

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -50.0 to 50.0 single section **Power Dissipation Rating Per Section In Watts:** 0.75 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a **Unit Of Measure: Demilitarization:**