NSN 5905-00-145-3895

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-145-3895

Section Quantity:
1
Body Style:
Rectangular w/mounting holes
Reliability Indicator:
Not established
Overall Length:
0.723 inches
Terminal Length:
0.187 inches
Overall Height:
0.500 inches
Overall Width:
0.215 inches
Mounting Hole Diameter:
0.075 inches
Shaft Diameter:
0.036 inches
Shaft Length:
0.078 inches
Body Length:
0.500 inches
Body Width:
0.215 inches
Body Height:
0.500 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Center To Center Distance Between Terminals:
0.200 inches
Lateral Distance Between Mounting Hole Centers:
0.523 inches
Mounting Facility Quantity:
2
Terminal Location:
Left adjacent side from adjustment control
Mounting Method:
Unthreaded holes and pins
Center To Center Distance Between Terminal Rows:

0.100 inches

NSN 5905-00-145-3895

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section: 5.000 kilohms single section

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-250.0 to 250.0 single section

Power Dissipation Rating Per Section In Watts:

0.75 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0