# NSN 5905-00-145-5425

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-145-5425

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.010
Overall Length:
0.470 inches
Terminal Length:
0.300 inches
Overall Height:
0.375 inches
Overall Width:
0.317 inches
Shaft Diameter:
0.075 inches
Shaft Length:
0.080 inches
Body Length:
0.375 inches
Body Width:
0.182 inches
Body Height:
0.375 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 5400.0 and 10800.0
Center To Center Distance Between Terminals:
0.200 inches
Fragility Factor:
Moderately delicate
Terminal Location:
Left adjacent side two rows
Mounting Method:
Terminal
Center To Center Distance Between Terminal Rows:
0.100 inches

## NSN 5905-00-145-5425

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



10.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:** 

Between 5400.0 and 10800.0

**Center To Center Distance Between Center Terminal And Outside Terminal:** 

0.100 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 single section

**Power Dissipation Rating Per Section In Watts:** 

0.75 free air single section

**Resistance Tolerance Per Section In Percent:** 

-5.0 to 5.0 single section

**Actuator Travel Control Feature:** 

Clutch

**Criticality Code Justification:** 

Feat

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

**Standard Taper Curve Per Section:** 

A single section

## **Special Features:**

Support equipment, h-3 helicopter; counter measure set, an/slq-32; support equipment, b-1 aircraft; telephone terminal an/tcc-72; missile, air to air, pheonix (aim-54); missile, all weather anti-ship harpoon (agm-84); missile, air to surface, walleye-erdl; radio terminal set an/srq-4; radio set an/brc-201; deep submergence system (dssp); tactical data system an/uya-4c (v); helicopter, advance attack, ah-1w, radar set It air traffic control (17m jul83) an/tps-63; radar bomb directing set an/tpb-1d; maneuver control system, an/uyq-30, an/uyq-30a; hawk missile mim-23

#### **Test Data Document:**

81349-mil-r-39015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Terminal Type And Quantity:**

3 pin

**Specification Data:** 

81349-mil-r-39015/3 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0