

View Online at <https://aerobasegroup.com/nsn/5905-00-146-5112>

Section Quantity:

1

Body Style:

Cylindrical tab/flange mounted

Reliability Indicator:

Not established

Mounting Hole Diameter:

Between 0.133 inches and 0.139 inches

Actuator Type:

Flush drive with slot-hole

Maximum Running Torque:

10.00 inch-ounces

Distance Between Mounting Hole Centers:

1.000 inches

Mounting Facility Quantity:

2

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Unthreaded hole

Features Provided:

Grounded contact arm

Electrical Resistance Per Section:

3.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

246.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

Power Dissipation Rating Per Section In Watts:

1.5 free air single section and 2.0 heat sink single section

Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0