

View Online at <https://aerobasegroup.com/nsn/5905-00-146-5112>

**Section Quantity:**

1

**Body Style:**

Cylindrical tab/flange mounted

**Reliability Indicator:**

Not established

**Mounting Hole Diameter:**

Between 0.133 inches and 0.139 inches

**Actuator Type:**

Flush drive with slot-hole

**Maximum Running Torque:**

10.00 inch-ounces

**Distance Between Mounting Hole Centers:**

1.000 inches

**Mounting Facility Quantity:**

2

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Grounded contact arm

**Electrical Resistance Per Section:**

3.000 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

246.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

105.0 single section

**Power Dissipation Rating Per Section In Watts:**

1.5 free air single section and 2.0 heat sink single section

**Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

**Actuator Travel Control Feature:**

Stops

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

55.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0