## NSN 5905-00-146-5816

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-146-5816 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.312 inches **Terminal Length:** 11.500 inches **Overall Height:** 0.315 inches **Overall Width:** 0.250 inches **Mounting Hole Diameter:** 0.086 inches **Shaft Diameter:** 0.062 inches **Shaft Length:** 0.125 inches **Body Length:** 1.250 inches **Body Width:** 0.250 inches **Body Height:** 0.315 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Maximum Running Torque:** 7.50 inch-ounces **Lateral Distance Between Mounting Hole Centers:** 1.000 inches **Mounting Facility Quantity: Terminal Location:** Rear end

**Mounting Method:**Unthreaded hole

**Electrical Resistance Per Section:** 

5.000 megohms single section

## NSN 5905-00-146-5816

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Rotary Actuator Travel In Angular Deg:                                      |
|---|
| 7920.0  |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 135.0 single section  |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:   |
| -800.0 to 50.0 single section   |
| Power Dissipation Rating Per Section In Watts:                              |
| 0.25 free air single section  |
| Resistance Tolerance Per Section In Percent:                                |
| -20.0 to 20.0 single section  |
| Actuator Travel Control Feature:  |
| Stops   |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:         |
| 50.0 single section   |
| Standard Taper Curve Per Section:   |
| A single section  |
| Terminal Type And Quantity:   |
| 3 wire lead   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |