

View Online at <https://aerobasegroup.com/nsn/5905-00-146-9464>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Body Diameter:

1.156 inches

Mounting Bushing Length:

0.250 inches

Body Length:

1.312 inches

Shaft Bearing Type:

Bearing

Actuator Type:

Dual concentric

Maximum Starting Torque:

6.00 inch-ounces

Maximum Stop Torque:

192.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

5.000 kilohms 2nd section and 10.000 kilohms 1st section

Rotary Actuator Travel In Angular Deg:

Between 309.0 and 315.0

Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 all sections

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0