## NSN 5905-00-146-9984

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-146-9984

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:                                                                                   |
|-------------------------------------------------------------------------------------------------------------------------------------------------|
| -20.0/+20.0                                                                                                                                     |
| Electrical Resistance:                                                                                                                          |
| 100.000 ohms                                                                                                                                    |
| Resistance Tolerance In Percent:                                                                                                                |
| -1.000 to 1.000                                                                                                                                 |
| Ambient Tempurature In Deg Celsius At Full Rated Power:                                                                                         |
| 25.0                                                                                                                                            |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:                                                                                 |
| 275.0                                                                                                                                           |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:                                                                                    |
| -55.0/+275.0                                                                                                                                    |
| Inclosure Method:                                                                                                                               |
| Encapsulated                                                                                                                                    |
| Terminal Type:                                                                                                                                  |
| Wire lead                                                                                                                                       |
| Reliability Indicator:                                                                                                                          |
| Established                                                                                                                                     |
| Reliability Failure Rate Level In Percent:                                                                                                      |
| 1.000                                                                                                                                           |
| Body Diameter:                                                                                                                                  |
| 0.187 inches                                                                                                                                    |
| Body Length:                                                                                                                                    |
| 0.560 inches                                                                                                                                    |
| Power Dissipation Rating In Watts:                                                                                                              |
| 4.000 free air                                                                                                                                  |
| Style Designator:                                                                                                                               |
| Axial terminal each end                                                                                                                         |
| Test Data Document:                                                                                                                             |
| 06481-912111 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental       |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                                             |
| Shelf Life:                                                                                                                                     |
| N/a                                                                                                                                             |
| Unit Of Measure:                                                                                                                                |
|                                                                                                                                                 |
| Demilitarization:                                                                                                                               |
| No                                                                                                                                              |
| Fiig:                                                                                                                                           |
| A001a0                                                                                                                                          |