

View Online at <https://aerobasegroup.com/nsn/5905-00-147-1598>

Section Quantity:

1

Body Style:

Rectangular w/bushing/slot mounted

Reliability Indicator:

Not established

Mounting Slot Width:

0.093 inches

Shaft Diameter:

0.090 inches

Shaft Length:

0.250 inches

Mounting Bushing Length:

0.250 inches

Body Length:

0.430 inches

Body Width:

0.240 inches

Body Height:

0.450 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

9000.0

Lateral Distance Between Mounting Hole Centers:

0.419 inches

Screw Thread Diameter:

0.190 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Mounting Facility Quantity:

2

Terminal Location:

Rear end

Mounting Method:

Standard bushing and slot

Electrical Resistance Per Section:

500.0 ohms single section

Rotary Actuator Travel In Angular Deg:

9000.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0