NSN 5905-00-147-1863

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-147-1863 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Overall Length:** Between 0.435 inches and 0.450 inches **Body Diameter:** 0.250 inches **Body Length:** Between 0.185 inches and 0.200 inches **Overall Diameter:** 0.250 inches **Actuator Type:** Flush drive with slot-hole **Maximum Starting Torque:** 5.00 inch-ounces **Terminal Location:** Rear end **Mounting Method: Terminal Electrical Resistance Per Section:** 20.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 270.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0 to 100.0 single section **Power Dissipation Rating Per Section In Watts:** 0.75 free air single section **Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 75.0 single section **Standard Taper Curve Per Section:** A single section

Terminal Type And Quantity:

3 wire lead

NSN 5905-00-147-1863

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A002a0