## NSN 5905-00-147-6100

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-147-6100

Electrical Resistance: 21.500 kilohms Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Body Diameter: Between 0.344 inches and 0.437 inches Bedween 0.344 inches and 1.124 inches Power Dissipation Rating In Watts: -1.000 free air Style Designator: Axial terminal each end Test Data Document: 95542-937-223 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etcesculades any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/A Unit Of Measure:	
excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Body Diameter: Bettween 0.344 inches and 0.437 inches Between 0.344 inches and 1.124 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 95542-937-223 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a Unit Of Measure:	50.0 to 50.0
Resistance Tolerance In Percent: -1.000 to 1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead  Body Diameter: Between 0.344 inches and 0.437 inches  Bedween 0.344 inches and 1.124 inches  Power Dissipation Rating In Watts: 1.000 free air  Style Designator: Axial terminal each end Test Data Document: 95542-937-223 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etce excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0  Inclosure Method: Encapsulated Terminal Type: Wire lead Body Diameter: Between 0.344 inches and 0.437 inches Between 0.344 inches and 0.437 inches Between 1.000 inches and 1.124 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 95542-937-223 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	21.500 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0 to 175.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Body Diameter:  Between 0.344 inches and 0.437 inches  Body Length:  Between 1.000 inches and 1.124 inches  Power Dissipation Rating In Watts:  1.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  95542-937-223 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0 to 175.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Body Diameter:  Between 0.344 inches and 0.437 inches  Bedween 0.344 inches and 1.124 inches  Power Dissipation Rating In Watts:  1.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  95542-937-223 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	1.000 to 1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0 to 175.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Body Diameter:  Between 0.344 inches and 0.437 inches  Between 0.344 inches and 1.124 inches  Power Dissipation Rating In Watts:  1.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  95542-937-223 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 1.000 inches and 1.124 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 95542-937-223 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0 to 175.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead  Body Diameter: Between 0.344 inches and 0.437 inches  Body Length: Between 1.000 inches and 1.124 inches  Power Dissipation Rating In Watts: 1.000 free air  Style Designator: Axial terminal each end  Test Data Document: 95542-937-223 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Encapsulated Terminal Type: Wire lead Body Diameter: Between 0.344 inches and 0.437 inches Between 1.000 inches and 1.124 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 95542-937-223 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	175.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 1.000 inches and 1.124 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 95542-937-223 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etcexcludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 1.000 inches and 1.124 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 95542-937-223 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etcexcludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	55.0 to 175.0
Terminal Type:  Wire lead  Body Diameter:  Between 0.344 inches and 0.437 inches  Body Length:  Between 1.000 inches and 1.124 inches  Power Dissipation Rating In Watts:  1.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  95542-937-223 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etcexcludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	nclosure Method:
Wire lead  Body Diameter: Between 0.344 inches and 0.437 inches  Body Length: Between 1.000 inches and 1.124 inches  Power Dissipation Rating In Watts: 1.000 free air  Style Designator: Axial terminal each end  Test Data Document: 95542-937-223 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etcexcludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:	Encapsulated
Between 0.344 inches and 0.437 inches  Between 1.000 inches and 1.124 inches  Power Dissipation Rating In Watts:  1.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  95542-937-223 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Terminal Type:
Between 0.344 inches and 0.437 inches  Body Length:  Between 1.000 inches and 1.124 inches  Power Dissipation Rating In Watts:  1.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  95542-937-223 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Wire lead
Between 1.000 inches and 1.124 inches  Power Dissipation Rating In Watts:  1.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  95542-937-223 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etcexcludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Body Diameter:
Between 1.000 inches and 1.124 inches  Power Dissipation Rating In Watts:  1.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  95542-937-223 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Between 0.344 inches and 0.437 inches
Power Dissipation Rating In Watts:  1.000 free air  Style Designator: Axial terminal each end  Test Data Document:  95542-937-223 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Body Length:
1.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  95542-937-223 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Between 1.000 inches and 1.124 inches
Style Designator:  Axial terminal each end  Test Data Document:  95542-937-223 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Power Dissipation Rating In Watts:
Axial terminal each end  Test Data Document:  95542-937-223 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	1.000 free air
Test Data Document:  95542-937-223 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Style Designator:
95542-937-223 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Test Data Document:
Shelf Life: N/a Unit Of Measure:	95542-937-223 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
N/a Unit Of Measure: 	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure:	Shelf Life:
- <del>-</del>	N/a
	Unit Of Measure:
Pomilitarization.	-
Deminicalization.	Demilitarization:
No	No
Fiig:	Filg:
A001a0	A001a0