NSN 5905-00-147-6814

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-147-6814 **Section Quantity: Body Style:** Cylindrical bushing mounted **Overall Length:** 1.689 inches **Body Diameter:** 1.094 inches **Shaft Diameter:** Between 0.248 inches and 0.251 inches **Shaft Length:** 1.202 inches **Mounting Bushing Length:** Between 0.344 inches and 0.390 inches **Body Length:** 0.562 inches **Overall Diameter:** 1.515 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 309.0 and 320.0 **Maximum Starting Torque:** 6.00 inch-ounces **Maximum Stop Torque:** 128.00 inch-ounces **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:**

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

NSN 5905-00-147-6814

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



500.000 ohms single section

Rotary Actuator Travel In Angular Deg:

Between 309.0 and 320.0

Resistance Tempurature Characteristic Range Per Section In Percent:

-3.0 to 0.0 -55 degrees celsius single section and -5.0 to 10.0 -25 degrees celsius single section and -5.0 to 10.0 25 degrees celsius single section and -0.0 to 3.0 120 degrees celsius single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

96214-750536 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0