## NSN 5905-00-147-7234

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-147-7234

20.000 hose Resistance: 20.000 ohms Resistance Tolerance In Percent: 5.000 to 5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0 to 350.0 Inclosure Method: Encased Reliability Indicator: Wire lead Reliability Indicator: Vot established Terminal Length: 20.328 inches 20.00 planeter: 20.328 inches 20.00 planeter: 20.328 inches 20.00 free air Style Designation Rating In Watts: 20.00 free air Style Designator: 25.01 to 350.0 inclosured Reliability (Indicator) 26.01 to 1678601 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: 25.01 to 1678601 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: 25.02 to 1678601 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: 25.03 to 1678601 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, should be such to 1678601 drawing, standard or other document that may be referenced in a basic governing drawing) 25.04 to 1678601 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: 25.05 to 1678601 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: 25.06 to 1678601 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: 25.07 to 1678601 drawing (this is the basic governing drawing)	empurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 5.000 to 5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 55.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 55.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 55.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 350.0 Tempurature Method: Temp	0.0 to 20.0
Resistance Tolerance In Percent: 5.000 to 5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 95.00 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 95.00 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 95.0 to 350.0 Inclosure Method: 96.00 Inclosure Metho	ectrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0 Tempurature Method: Encased Terminal Type: Wire lead Reliability Indicator: Vot established Terminal Length: 2.328 inches 28.04y Diameter: 3.328 inches 28.04y Length: 28.99 inches 28.04y Length: 28.90 inches 28.90	00.000 ohms
Ambient Tempurature In Deg Celsius At Full Rated Power:  25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  25.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius:  25.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius:  25.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius:  25.0 Tempurature Method:  25.0 26.0 26.0 26.0 26.0 26.0 26.0 26.0 26	esistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0 So.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0 So.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0 So.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0 So.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0 So.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0 So.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0 Selection Celsius:  150.0 Selection Celsius:  150.0 Office Selection Celsius:  150.0 Office Selection Celsius:  150.0 Selection Celsius:	.000 to 5.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  250.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  250.0 to 350.0  Inclosure Method:  Encased  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  20.312 inches  Body Diameter:  20.328 inches  Body Diameter:  20.328 inches  Body Length:  20.99 inches  Power Dissipation Rating In Watts:  Body Desginator:  Style De	mbient Tempurature In Deg Celsius At Full Rated Power:
Fempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0 to 350.0  Inclosure Method:  Encased  Ferminal Type:  Wire lead  Reliability Indicator:  Not established  Ferminal Length: 312 inches 304y Diameter: 328 inches 309 Jameter: 381 inches 399 ower Dissipation Rating In Watts: 5000 free air  Style Designator:  Axial terminals one end  Fest Data Document:  10001-1678601 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;  excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Sheff Life:  Va	5.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0 to 350.0  Inclosure Method:  Encased  Ferminal Type:  Wire lead  Reliability Indicator:  Not established  Ferminal Length: 312 inches  Body Diameter: 328 inches  Body Length: 389 inches  Power Dissipation Rating In Watts: 500 free air  Style Designator:  Axial terminals one end  Fest Data Document:  10001-1678601 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  Wa	mbient Tempurature In Deg Celsius At Zero Percent Rated Power:
solution of the state of the st	50.0
Inclosure Method: Encased Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 0.312 inches Body Diameter: 0.328 inches Body Diameter: 0.398 inches Body Length: 0.891 inches Power Dissipation Rating In Watts: 5.000 free air Byle Designator: Axial terminals one end Fest Data Document: 10001-1678601 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa	empurature Range Of Tempurature Coefficient In Deg Celsius:
Ferminal Type:  Wire lead  Reliability Indicator:  Not established  Ferminal Length:  0.312 inches  8.0dy Diameter:  0.328 inches  8.0dy Length:  0.891 inches  Power Dissipation Rating In Watts:  5.000 free air  Style Designator:  Axial terminals one end  Fest Data Document:  10001-1678601 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;  excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  Wa	5.0 to 350.0
Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:	closure Method:
Wire lead Reliability Indicator: Not established Ferminal Length: 0.312 inches Body Diameter: 0.328 inches Body Length: 0.891 inches Power Dissipation Rating In Watts: 0.000 free air Style Designator: Axial terminals one end Fest Data Document: 10001-1678601 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	ncased
Reliability Indicator: Not established Ferminal Length: 0.312 inches Body Diameter: 0.328 inches Body Length: 0.891 inches Power Dissipation Rating In Watts: 0.000 free air Style Designator: Axial terminals one end Fest Data Document: 10001-1678601 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	erminal Type:
Note established  Ferminal Length:  0.312 inches  Body Diameter:  0.328 inches  Body Length:  0.891 inches  Power Dissipation Rating In Watts:  5.000 free air  Style Designator:  Axial terminals one end  Fest Data Document:  10001-1678601 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;  excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  Wa	ire lead
Cerminal Length: 0.312 inches Cody Diameter: 0.328 inches Cody Length: 0.891 inches Cower Dissipation Rating In Watts: 0.6000 free air Cityle Designator: Axial terminals one end Cest Data Document: 10001-1678601 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: W/a	eliability Indicator:
2.312 inches 2.30dy Diameter: 2.328 inches 2.30dy Length: 2.891 inches 2.80dy Length: 2.891 inches 2.800 free air 2.5000 free air 2.51de Designator: 2.521de Designator: 2.521de Total Document: 2.521de Total Document: 2.5221de Total Document (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 2.5221de Total Document (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 2.5221de Total Document (this is the basic governing drawing) 3.5321de Total Document (this is the	ot established
Body Length:  0.8328 inches  Body Length:  0.891 inches  Power Dissipation Rating In Watts:  6.000 free air  Style Designator:  Axial terminals one end  Fest Data Document:  10001-1678601 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;  excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:	erminal Length:
0.328 inches  Body Length: 0.891 inches  Power Dissipation Rating In Watts: 5.000 free air  Style Designator: Axial terminals one end  Fest Data Document: 10001-1678601 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  W/a	312 inches
Body Length:  0.891 inches  Power Dissipation Rating In Watts:  5.000 free air  Style Designator:  Axial terminals one end  Fest Data Document:  10001-1678601 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;  excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:	ody Diameter:
Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminals one end Fest Data Document: 10001-1678601 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life:  N/a	328 inches
Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminals one end Fest Data Document: 1.0001-1678601 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 2.0001-1678601 drawing (this is the basic governing drawing) by the preferenced in a basic governing drawing)  Shelf Life:  N/a	ody Length:
Style Designator: Axial terminals one end Test Data Document: 10001-1678601 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life:	891 inches
Axial terminals one end  Test Data Document:  10001-1678601 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:	ower Dissipation Rating In Watts:
Axial terminals one end  Fest Data Document:  10001-1678601 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a	000 free air
Test Data Document: 10001-1678601 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a	yle Designator:
10001-1678601 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a	kial terminals one end
excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a	est Data Document:
Shelf Life: N/a	0001-1678601 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
N/a	cludes any specification, standard or other document that may be referenced in a basic governing drawing)
	nelf Life:
Jnit Of Measure:	'a
_	nit Of Measure:
Demilitarization:	emilitarization:
No	
Filg:	ig:
A001a0	001a0