## NSN 5905-00-148-4247

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-148-4247 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 0.6240 inches and 0.6250 inches Pilot Length: 0.0620 inches **Overall Length:** 1.375 inches **Undercut Diameter:** 0.781 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** Between 0.1245 inches and 0.1248 inches **Shaft Length:** 0.375 inches **Body Length:** 1.000 inches **Overall Diameter:** 1.098 inches **Mounting Lip Diameter:** 0.8750 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 1080.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Clamp ring

**Features Provided:** 

Nonmetallic shaft

## NSN 5905-00-148-4247

Precision Wire Wound Variable Resistor - Page 2 of 2



| Electrical Resistance Per Section:  |
|---|
| 666.667 ohms 2nd section  |
| Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation: |
| 772.2 all sections  |
| Rotary Actuator Travel In Angular Deg:  |
| 1080.0  |
| Function Conformity Tolerance Per Section:  |
| -2.00/+2.00 all sections  |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:           |
| -25.0 to 25.0 all sections  |
| Power Dissipation Rating Per Section In Watts:                                      |
| 0.25 free air all sections  |
| Function Conformity Per Section:  |
| All sections independent linearity  |
| Fixed Tap Quantity Per Section:   |
| 1 all sections  |
| Tap Location Tolerance Per Section:   |
| -50.0 to 50.0 ohms 1st section  |
| Resistance Tolerance Per Section In Percent:  |
| -5.0 to 5.0 all sections  |
| Actuator Travel Control Feature:  |
| Stops   |
| Tap Location From Ccw Terminal Per Section In Ohms:                                 |
| 333.3 all sections  |
| Function Characteristic Per Section:  |
| All sections linear   |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:                 |
| 85.0 all sections   |
| Terminal Type And Quantity:   |
| 8 turret  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A002a0  |