NSN 5905-00-149-8591

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-149-8591 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 1.3120 inches and 1.3125 inches Pilot Length: 0.0620 inches **Overall Length:** 1.255 inches **Undercut Diameter:** 1.312 inches **Undercut Width:** 0.0730 inches **Body Diameter:** 1.468 inches **Shaft Diameter:** Between 0.2495 inches and 0.2499 inches **Shaft Length:** Between 0.350 inches and 0.410 inches **Body Length:** 0.875 inches **Overall Diameter:** 1.860 inches **Mounting Lip Diameter:** Between 1.4270 inches and 1.4420 inches **Mounting Lip Depth:** 0.0930 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Maximum Starting Torque:** 1.00 inch-ounces **Shaft Runout:** 0.001 inches **Terminal Location:** Radially positioned over more than half the circumference

NSN 5905-00-149-8591

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Clamp ring
Fixed Tap Quantity Per Section:
2 single section
Actuator Travel Control Feature:
Stops
Terminal Type And Quantity:
5 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0