## NSN 5905-00-150-5543

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-150-5543 **Section Quantity: Body Style:** Rectangular w/mounting holes **Overall Length:** 1.036 inches **Terminal Length:** 0.500 inches **Overall Height:** 0.500 inches **Overall Width:** 0.192 inches **Mounting Hole Diameter:** Between 0.071 inches and 0.075 inches **Shaft Diameter:** 0.078 inches **Body Length:** 0.500 inches **Body Width:** 0.192 inches **Body Height:** 0.500 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Maximum Starting Torque:** 5.00 inch-ounces **Center To Center Distance Between Terminals:** 0.200 inches **Lateral Distance Between Mounting Hole Centers:** Between 0.520 inches and 0.526 inches **Mounting Facility Quantity: Terminal Location:** Rear end **Electrical Resistance Per Section:** 

1.0000 kilohms single section

**Rotary Actuator Travel In Angular Deg:** 

9000.0

## NSN 5905-00-150-5543

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -50.0 to 50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a **Unit Of Measure:** Demilitarization: