

View Online at <https://aerobasegroup.com/nsn/5905-00-150-5622>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Overall Length:

2.250 inches

Body Diameter:

1.562 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.875 inches

Body Length:

1.375 inches

Overall Diameter:

1.719 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

Maximum Starting Torque:

8.00 inch-ounces

Nonturn Device Location:

At 6 oclock

Nonturn Device Radius:

0.500 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

125.000 ohms single section

Rotary Actuator Travel In Angular Deg:

300.0

Power Dissipation Rating Per Section In Watts:

25.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Stops

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0