

View Online at <https://aerobasegroup.com/nsn/5905-00-151-4566>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.250 inches

First Flat Length:

0.344 inches

Flat Height:

0.219 inches

Body Diameter:

2.312 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.875 inches

Mounting Bushing Length:

0.375 inches

Body Length:

1.375 inches

Overall Diameter:

2.718 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

300.0

Maximum Starting Torque:

32.00 inch-ounces

Maximum Running Torque:

0.25 inch-ounces

Nonturn Device Location:

At 6 oclock

Nonturn Device Radius:

0.500 inches

Fragility Factor:

Rugged

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

0.2 ohms single section

Rotary Actuator Travel In Angular Deg:

300.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

340.0 single section

Power Dissipation Rating Per Section In Watts:

50.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0