## NSN 5905-00-152-9978

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-152-9978

Section Quantity:

1

Body Style:

Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:

0.250 inches

Shaft Length:

0.625 inches

**Mounting Bushing Length:** 

0.375 inches

0.328 inches

Shaft Diameter:

**Body Length:** 0.469 inches

Shaft Style:

Round, slotted

**Actuator Type:** 

Single shaft

Fragility Factor:

Moderately rugged

**Screw Thread Diameter:** 

0.375 inches

**Screw Thread Series Designator:** 

Unef

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Radially positioned over less than half the circumference

**Mounting Method:** 

Standard bushing

**Electrical Resistance Per Section:** 

2.0 kilohms single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

**Power Dissipation Rating Per Section In Watts:** 

1.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

## NSN 5905-00-152-9978

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



<b>Standard Taper Curve Per Section:</b>
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0