Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-153-6188

## Section Quantity:

1

Body Style:

Rectangular

# **Reliability Indicator:**

Not established

### **Overall Length:**

0.535 inches

#### Terminal Length:

0.155 inches

#### **Overall Height:**

0.434 inches

#### **Overall Width:**

0.298 inches

### Body Length:

#### 0.380 inches

Body Width:

0.298 inches

# Body Height:

0.434 inches

### Actuator Type:

Flush drive with slot-hole

### Maximum Running Torque:

5.00 inch-ounces

### **Center To Center Distance Between Terminals:**

0.300 inches

### **Terminal Location:**

Lower adjacent side single row

### **Mounting Method:**

Terminal

### **Electrical Resistance Per Section:**

2.0 kilohms single section

### **Rotary Actuator Travel In Angular Deg:**

270.0

### Center To Center Distance Between Center Terminal And Outside Terminal:

0.150 inches

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

## Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-150.0 to 150.0 single section

# Power Dissipation Rating Per Section In Watts:

0.5 free air single section



## **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

## Actuator Travel Control Feature:

Stops

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0