NSN 5905-00-153-7510

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-153-7510 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.75000 inches Pilot Length: 0.06200 inches **Overall Length:** 1.750 inches **Undercut Diameter:** 0.781 inches **Undercut Width:** 0.06200 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** Between 0.1245 inches and 0.1248 inches **Shaft Length:** 0.500 inches **Body Length:** 0.770 inches **Overall Diameter:** 1.188 inches **Mounting Lip Diameter:** 0.87500 inches **Mounting Lip Depth:** 0.06200 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 354.0 **Maximum Starting Torque:**

0.10 inch-ounces

0.10 inch-ounces

Maximum Running Torque:

NSN 5905-00-153-7510

Shaft End Play:

Precision Wire Wound Variable Resistor - Page 2 of 3



0.00400 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.00150 inches
Shaft Radial Play:
0.002 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
20.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.20 to 0.20 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
1.25 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Tap Location From Ccw Terminal Per Section In Ohms:
10000.0 single section
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
-20.0/+20.0 Single Section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
-

4 turret

NSN 5905-00-153-7510

Precision Wire Wound Variable Resistor - Page 3 of 3



Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0