Nonprecision Wire Wound Variable Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-153-9555

Section Quar	ntity:
1	
Actuator Typ	e:
Single shaft	
Maximum Sta	arting Torque:
5.00 inch-ound	Ces
Mounting Fac	cility Quantity:
1	
Electrical Res	sistance Per Section:
10.000 kilohm	s single section
Rotary Actua	tor Travel In Angular Deg:
9000.0	
Ambient Tem	purature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single s	ection
Tempurature	Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0 to 50.0 s	single section
Power Dissip	ation Rating Per Section In Watts:
1.0 free air sin	gle section
Resistance T	olerance Per Section In Percent:
-5.0 to 5.0 sing	gle section
Actuator Trav	vel Control Feature:
Clutch	
Ambient Tem	purature In Deg Celsius Per Section At Full Rated Power:
70.0 single se	ction
Standard Tap	er Curve Per Section:
A single section	n
Test Data Do	cument:
95542-138-19	2 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any :	specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Typ	e And Quantity:
3 pin	
Shelf Life:	
N/a	
Unit Of Meas	ure:
Demilitarizati	on:
No	
Fiig:	
A002a0	