## NSN 5905-00-154-3985

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-154-3985 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.7500 inches Pilot Length: 0.0620 inches **Overall Length:** 1.645 inches **Undercut Diameter:** 0.781 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.1248 inches **Shaft Length:** 0.875 inches **Body Length:** 0.770 inches **Overall Diameter:** 1.032 inches **Mounting Lip Diameter:** 0.8750 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 354.0 **Maximum Starting Torque:** 

0.10 inch-ounces

0.10 inch-ounces

**Maximum Running Torque:** 



## NSN 5905-00-154-3985

Precision Wire Wound Variable Resistor - Page 2 of 3



| Objets Ford Plans  |
|--|
| Shaft End Play:  |
| 0.004 inches   |
| Shaft Runout:  |
| 0.001 inches   |
| Lateral Runout:  |
| 0.002 inches   |
| Pilot Diameter Runout:   |
| 0.0015 inches  |
| Shaft Radial Play:   |
| 0.002 inches   |
| Terminal Location:   |
| Radially positioned over less than half the circumference  |
| Mounting Method:   |
| Clamp ring   |
| Electrical Resistance Per Section:   |
| 2.0 kilohms single section   |
| Rotary Actuator Travel In Angular Deg:   |
| 360.0  |
| Function Conformity Tolerance Per Section:   |
| -0.25 to 0.25 single section   |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:  |
| 125.0 single section   |
| Power Dissipation Rating Per Section In Watts:   |
| 1.25 free air single section   |
| Function Conformity Per Section:   |
| Single section independent linearity   |
| Resistance Tolerance Per Section In Percent:   |
| -5.0/+5.0 single section   |
| Actuator Travel Control Feature:   |
| Continuous motion  |
| Function Characteristic Per Section:   |
| Single section linear  |
| Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:   |
| -0.0/+20.0 single section  |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:  |
| 70.0 single section  |
| Test Data Document:  |
| 49671-2189955 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing)                              |
| Terminal Type And Quantity:  |
| 3 turret   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |

-

## NSN 5905-00-154-3985

Precision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0