NSN 5905-00-155-6984

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-155-6984 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 3.125 inches First Flat Length: 0.625 inches Flat Height: 0.216 inches **Body Diameter:** 1.281 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 2.500 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.625 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:**

Standard bushing

Electrical Resistance Per Section:

25.000 ohms single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

NSN 5905-00-155-6984

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance	Tolerance	Per	Section	In	Percent:

-10.0 to 10.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0