NSN 5905-00-155-8736

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-155-8736

-100.0i+100.0 Electrical Resistance: 24.900 kilohms Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.055 inches Body Diameter: 0.155 inches Body Langth: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Akial terminal each end Test Data Document: 94756-443-0969 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Demilitarization: No Flig:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Electrical Resistance: 24 900 kilohms Resistance Tolerance in Percent: -1.000 to 1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0 to 175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.0001 Body Diameter: 0.155 inches Body Length: 0.281 inches Power Dissipation Rating in Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94755-443-0969 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shoft Life: No Demilitarization: No Filig:	
24.900 kilohms Resistance Tolerance in Percent: -1.000 to 1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0 to 175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.0001 Body Diameter: 0.155 inches Body Length: 0.281 inches Power Dissipation Rating in Watts: 0.125 free air Style Designator: Akial terminal each end Test Data Document: 94756-443-0969 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Umit Of Measure:	
Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0 Inclosure Method: -Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0001 Body Diameter: 0.155 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0969 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0001 Body Diameter: 0.155 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0969 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0001 Body Diameter: 0.155 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.128 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0969 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0001 Body Diameter: 0.155 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94766-443-0969 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Faiture Rate Level In Percent: 0.0001 Body Diameter: 0.155 inches Body Dameter: 0.155 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0969 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a Unit Of Measure: Demilitarization: No Filg:	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Faiture Rate Level In Percent: 0.0001 Body Diameter: 0.155 inches Body Dameter: 0.155 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0969 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a Unit Of Measure: Demilitarization: No Filg:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0001 Body Diameter: 0.155 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0969 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure: Demilitarization: No Flig:	175.0
Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0001 Body Diameter: 0.155 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0969 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0001 Body Diameter: 0.155 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0969 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	-55.0 to 175.0
Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0001 Body Diameter: 0.155 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0969 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Inclosure Method:
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0001 Body Diameter: 0.155 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0969 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Hermetically sealed
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0001 Body Diameter: 0.155 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0969 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Terminal Type:
Established Reliability Failure Rate Level In Percent: 0.0001 Body Diameter: 0.155 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0969 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Wire lead
Reliability Failure Rate Level In Percent: 0.0001 Body Diameter: 0.155 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0969 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Reliability Indicator:
Body Diameter: 0.155 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0969 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Established
Body Diameter: 0.155 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0969 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Failure Rate Level In Percent:
0.155 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0969 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.0001
Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0969 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Diameter:
0.281 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0969 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.155 inches
Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0969 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
O.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0969 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.281 inches
Style Designator: Axial terminal each end Test Data Document: 94756-443-0969 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 94756-443-0969 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.125 free air
Test Data Document: 94756-443-0969 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
94756-443-0969 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	94756-443-0969 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc
N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Filg:	Unit Of Measure:
No Filg:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0