Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-155-8765

Section Quantity:

1

Body Style:

Rectangular w/mounting holes

Reliability Indicator:

Not established

Overall Length:

1.020 inches

Terminal Length:

0.500 inches

Overall Height:

0.500 inches

Overall Width:

0.220 inches

Mounting Hole Diameter:

0.078 inches

Shaft Diameter:

0.083 inches

Shaft Length:

0.030 inches

Body Length:

0.500 inches

Body Width:

0.220 inches

Body Height:

0.500 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Maximum Starting Torque:

5.00 inch-ounces

Maximum Running Torque:

5.00 inch-ounces

Center To Center Distance Between Terminals:

0.200 inches

Lateral Distance Between Mounting Hole Centers:

0.520 inches

Mounting Facility Quantity:

2

Terminal Location:

Rear end



Mounting Method: Terminal and unthreaded hole **Electrical Resistance Per Section:** 20.0 ohms single section **Rotary Actuator Travel In Angular Deg:** 9000.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -30.0 to 30.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Test Data Document:** 95542-138-062 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 3 pin Shelf Life: N/a Unit Of Measure: **Demilitarization:** Fiig: A002a0

No