NSN 5905-00-156-0602

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-156-0602

Electrical Resistance: 1.620 kilohms Resistance Tolerance In Percent: 0.100 to 0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 1.25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 1.75.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001
Resistance Tolerance In Percent: 0.100 to 0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent:
Resistance Tolerance In Percent: 0.100 to 0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent:
O.100 to 0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: I25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: I75.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Inclosure Method: Encapsulated Iferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent:
Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 nclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent:
55.0 to 175.0 nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent:
Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent:
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent:
Reliability Indicator: Established Reliability Failure Rate Level In Percent:
Established Reliability Failure Rate Level In Percent:
Reliability Failure Rate Level In Percent:
).001
······
Body Diameter:
0.188 inches
Body Length:
0.625 inches
Power Dissipation Rating In Watts:
0.250 free air
Style Designator:
Axial terminal each end
Test Data Document:
31349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Fiig:
A001a0