NSN 5905-00-156-7085

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-156-7085 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 0.6245 inches and 0.6250 inches Pilot Length: 0.0620 inches **Overall Length:** 3.522 inches **Undercut Width:** 0.0570 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** Between 0.124 inches and 0.1248 inches **Shaft Length:** Between 0.375 inches and 0.438 inches **Body Length:** 3.031 inches **Overall Diameter:** 0.875 inches **Mounting Lip Diameter:** 0.8750 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Shaft End Play:** 0.005 inches **Shaft Radial Play:** 0.002 inches **Mounting Method:** Clamp ring

Electrical Resistance Per Section:

20.0 kilohms 1st section

NSN 5905-00-156-7085

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation	Rating	Per	Section	ln	Watts
0.1 free air all section	ns				

Resistance Tolerance Per Section In Percent:

-2.0 to 2.0 2nd section

Shelf Life:

N/a

. ., -.

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0