

View Online at <https://aerobasegroup.com/nsn/5905-00-156-7099>

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 0.6247 inches and 0.6250 inches

Pilot Length:

0.0620 inches

Overall Length:

3.591 inches

Undercut Width:

0.0620 inches

Body Diameter:

0.875 inches

Shaft Diameter:

Between 0.1247 inches and 0.125 inches

Shaft Length:

Between 0.469 inches and 0.531 inches

Body Length:

3.060 inches

Overall Diameter:

0.875 inches

Mounting Lip Diameter:

0.8750 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

Maximum Starting Torque:

1.20 inch-ounces

Shaft End Play:

0.002 inches

Shaft Runout:

0.003 inches

Pilot Diameter Runout:

0.002 inches

Shaft Radial Play:

0.002 inches

Terminal Location:

Longitudinally positioned on the circumference

Electrical Resistance Per Section:

10.0 kilohms 1st section

Power Dissipation Rating Per Section In Watts:

0.1 free air all sections

Resistance Tolerance Per Section In Percent:

-1.0/+1.0 all sections

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0