NSN 5905-00-158-4621

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-158-4621

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-260.0/+260.0
Electrical Resistance:
2.500 kilohms
Resistance Tolerance In Percent:
-5.000 to 5.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
275.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+275.0
Inclosure Method:
Encapsulated
Terminal Type:
Tab, solder lug
Reliability Indicator:
Not established
Terminal Length:
0.532 inches
Body Length:
Between 1.938 inches and 2.062 inches
Body Width:
1.187 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
Between 2.719 inches and 2.781 inches
Power Dissipation Rating In Watts:
22.000 free air
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
2.750 inches
Terminal Width:
Between 0.172 inches and 0.265 inches
Mounting Hole Size:
Between 0.146 inches and 0.246 inches
Cubic Measure (non-core):
0.307 cubic inches
Unpackaged Unit Weight:
13.5 grams
Style Designator:

Test Data Document:

Terminals one edge

81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5905-00-158-4621

Inductive Wire Wound Fixed Resistor - Page 2 of 2



	Sı	peci	fica	tion	Data
--	----	------	------	------	------

81349-mil-r-26/2 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0