NSN 5905-00-158-5430

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-158-5430 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.625 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 3.375 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.562 inches **Shaft Style:** Round, square channelled **Actuator Type:** Single shaft **Fragility Factor:** Moderately rugged **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

3.0 kilohms single section

Power Dissipation Rating Per Section In Watts:

4.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Standard Taper Curve Per Section:

A single section

Special Features:

With mallory type 396 dial plate

NSN 5905-00-158-5430

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity	y:
----------------------------	----

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0