NSN 5905-00-158-5741

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-158-5741

Section Quantity:
2
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.312 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.875 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.875 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Fragility Factor:
Moderately rugged
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
150.0 ohms all sections
Power Dissipation Rating Per Section In Watts:
4.0 free air all sections
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 all sections
Standard Taper Curve Per Section:
A all sections

Special Features:

Ea section within 1 pct of ea other in values

NSN 5905-00-158-5741

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0