NSN 5905-00-158-5854

Section Quantity:

Cylindrical bushing mounted

Reliability Indicator:

Not established **Body Diameter:**1.156 inches **Shaft Diameter:**0.250 inches

Body Style:

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-158-5854

Shaft Length:
1.438 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.562 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 3 oclock
Nonturn Device Radius:
0.531 inches
Fragility Factor:
Moderately rugged
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
5.0 kilohms single section
Power Dissipation Rating Per Section In Watts:
5.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section

NSN 5905-00-158-5854

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section
A single section
Terminal Type And Quantity:
3 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0