Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-158-6509

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

#### **Overall Length:**

3.125 inches

#### First Flat Length:

2.000 inches

#### Flat Height:

0.216 inches

#### Body Diameter:

1.281 inches

#### Shaft Diameter:

0.250 inches

# Shaft Length:

2.500 inches

# Mounting Bushing Length:

0.375 inches

#### Body Length:

0.625 inches

#### Shaft Style:

Round, flatted

#### Actuator Type:

Single shaft

#### **Nonturn Device Location:**

At 9 oclock

#### Nonturn Device Radius:

0.531 inches

### Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

### Screw Thready Qty Per Inch (tpi):

32.0

### **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

1.000 kilohms single section



**Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section Standard Taper Curve Per Section: A single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A002a0