Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-158-7529

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.332 inches

Body Diameter:

1.680 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.875 inches

Mounting Bushing Length:

0.375 inches

Body Length:

1.410 inches

Overall Diameter:

2.250 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Maximum Starting Torque:

4.00 inch-ounces

Maximum Stop Torque:

2.40 inch-ounces

Nonturn Device Location:

At 12 oclock

Nonturn Device Radius:

0.500 inches

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0



specification type data in specification format; general type data on certain environmental

etc.).

Terminal Location:	
Lower adjacent side two rows	
Mounting Method:	
Standard bushing	
Center To Center Distance Between Terminal Row	vs:
0.188 inches	
Features Provided:	
Humidity proof	
Electrical Resistance Per Section:	
500.0 ohms single section	
Rotary Actuator Travel In Angular Deg:	
290.0	
Ambient Tempurature In Deg Celsius Per Section	At Zero Percent Rated Power:
340.0 single section	
Power Dissipation Rating Per Section In Watts:	
25.0 heat sink single section	
Resistance Tolerance Per Section In Percent:	
-0.5 to 0.5 single section	
Actuator Travel Control Feature:	
Stops	
Ambient Tempurature In Deg Celsius Per Section	At Full Rated Power:
25.0 single section	
Standard Taper Curve Per Section:	
A single section	
Test Data Document:	
81349-mil-r-22 specification (includes engineering typ	be bulletins, brochures, etc., that reflect s
excludes commercial catalogs, industry directories,	and similar trade publications, reflecting
and performance requirements and test conditions th	at are shown as "typical", "average", "",
Terminal Type And Quantity:	
3 tab, solder lug	
Specification Data:	
81349-mil-r-22/3 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A002a0	