

View Online at <https://aerobasegroup.com/nsn/5905-00-159-7291>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

Between 0.4365 inches and 0.4375 inches

**Pilot Length:**

Between 0.0570 inches and 0.0670 inches

**Undercut Diameter:**

Between 0.370 inches and 0.380 inches

**Undercut Width:**

Between 0.0570 inches and 0.0670 inches

**Body Diameter:**

0.495 mils and 0.505 centimeters

**Shaft Diameter:**

Between 0.1248 inches and 0.1251 inches

**Shaft Length:**

Between 0.690 inches and 0.710 inches

**Body Length:**

Between 0.620 inches and 0.630 inches

**Mounting Lip Diameter:**

Between 0.4950 inches and 0.5050 inches

**Mounting Lip Depth:**

0.0570 mils and 0.0670 centimeters

**Shaft Style:**

Round

**Shaft Bearing Type:**

Ball

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

350.0

**Maximum Starting Torque:**

0.075 inch-ounces

**Maximum Running Torque:**

0.05 inch-ounces

**Maximum Stop Torque:**

80.00 inch-ounces

**Shaft End Play:**

0.004 inches

**Shaft Runout:**

0.002 inches

**Lateral Runout:**

0.002 inches

**Pilot Diameter Runout:**

0.002 inches

**Shaft Radial Play:**

0.002 inches

**Fragility Factor:**

Moderately rugged

**Terminal Location:**

Rear end

**Mounting Method:**

Clamp ring

**Features Provided:**

Humidity proof

**Cubic Measure:**

0.123 cubic inches

**Electrical Resistance Per Section:**

10.0 percent, rated amperes c and better flooring

**Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:**

150.0 single section

**Rotary Actuator Travel In Angular Deg:**

360.0

**Function Conformity Tolerance Per Section:**

-1.00/+1.00 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-20.0/+20.0 single section

**Power Dissipation Rating Per Section In Watts:**

2.0 7th secondary quality

**Function Conformity Per Section:**

Single section independent linearity

**Fixed Tap Quantity Per Section:**

1 single section

**Tap Location Tolerance Per Section:**

-5.0/+5.0 ohms single section

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Tap Location From Ccw Terminal Per Section In Ohms:**

5000.0 single section

**Function Characteristic Per Section:**

7 o'clock all primaries

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 single section

**Terminal Type And Quantity:**

4 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0