

View Online at <https://aerobasegroup.com/nsn/5905-00-160-1445>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Overall Length:

1.334 inches

Terminal Length:

0.375 inches

Body Diameter:

Between 0.631 inches and 0.641 inches

Shaft Diameter:

Between 0.1235 inches and 0.1245 inches

Shaft Length:

0.750 inches

Mounting Bushing Length:

0.250 inches

Body Length:

0.584 inches

Overall Diameter:

Between 0.631 inches and 0.641 inches

Shaft Style:

Round

Switch Type:

Rotary

Switch Voltage Rating In Volts:

115.0

Actuator Type:

Single shaft

Nonturn Device Location:

At 3 oclock and at 9 oclock

Nonturn Device Radius:

0.375 inches

Switch Operating Position:

End of rotation

Switch Contact Arrangement:

Single pole, single throw, normally closed

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Switch

Electrical Resistance Per Section:

2.500 kilohms single section

Rotary Actuator Travel In Angular Deg:

Between 280.0 and 290.0

Power Dissipation Rating Per Section In Watts:

0.25 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Switch Current Type And Rating In Amps:

0.250 ac

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0