## NSN 5905-00-160-5229

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-160-5229 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.328 inches **Body Diameter:** 0.938 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.453 inches **Overall Diameter:** 1.258 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Features Provided:** Humidity proof

**Electrical Resistance Per Section:** 

1.000 kilohms single section

**Rotary Actuator Travel In Angular Deg:** 

300.0

## NSN 5905-00-160-5229

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
|---|
| 85.0 single section   |
| Power Dissipation Rating Per Section In Watts:                              |
| 0.5 heat sink single section  |
| Resistance Tolerance Per Section In Percent:                                |
| -30.0 to 30.0 single section  |
| Actuator Travel Control Feature:  |
| Stops   |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:         |
| 55.0 single section   |
| Standard Taper Curve Per Section:   |
| A single section  |
| Terminal Type And Quantity:   |
| 3 tab, solder lug   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |