NSN 5905-00-161-3040

Section Quantity:

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-161-3040

1
Body Style:
Rectangular
Reliability Indicator:
Not established
Overall Length:
0.470 inches
Overall Height:
0.375 inches
Overall Width:
0.532 inches
Shaft Diameter:
0.075 inches
Shaft Length:
0.080 inches
Body Length:
0.375 inches
Body Width:
0.160 inches
Body Height:
0.375 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Center To Center Distance Between Terminals:
0.200 inches
Fragility Factor:
Moderately delicate
Terminal Location:
Left adjacent side two rows
Mounting Method:
Terminal
Center To Center Distance Between Terminal Rows:
0.100 inches
Electrical Resistance Per Section:
1.0 kilohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

NSN 5905-00-161-3040

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Tempurature Coe	fficient Of Resistand	ce Per Section In	n Ppm Per D	eg Celsius:
-----------------	-----------------------	-------------------	-------------	-------------

-50.0 to 50.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

18876-11040688 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0