NSN 5905-00-162-8149

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-162-8149 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Overall Length:** 0.455 inches **Terminal Length:** 0.188 inches **Overall Height:** 0.375 inches **Overall Width:** 0.423 inches **Mounting Hole Diameter:** 0.075 inches **Shaft Diameter:** 0.080 inches **Shaft Length:** 0.093 inches **Body Length:** 0.375 inches **Body Width:** 0.235 inches **Body Height:** 0.375 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 8280.0 **Maximum Starting Torque:** 5.00 inch-ounces

Center To Center Distance Between Terminals:

0.200 inches

Lateral Distance Between Mounting Hole Centers:

0.375 inches

Mounting Facility Quantity:

Terminal Location:

Left adjacent side from adjustment control

NSN 5905-00-162-8149

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Unthreaded holes and pins
Center To Center Distance Between Terminal Rows:
0.100 inches
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
10.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
8280.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0 to 50.0 single section
Power Dissipation Rating Per Section In Watts:
0.75 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Continuous motion
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0