Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-163-2008

# Section Quantity:

1

Body Style:

Rectangular

# Reliability Indicator:

Not established

## Shaft Diameter:

0.100 inches

#### Shaft Length:

0.070 inches

#### **Body Length:**

0.750 inches

#### Body Width:

0.160 inches

#### **Body Height:**

# 0.360 inches

# Shaft Style:

Round, slotted

## Actuator Type:

Single shaft

#### Maximum Starting Torque:

5.00 inch-ounces

#### **Center To Center Distance Between Terminals:**

0.500 inches

#### **Terminal Location:**

Lower adjacent side two rows

#### **Mounting Method:**

Terminal

#### Center To Center Distance Between Terminal Rows:

0.200 inches

#### **Features Provided:**

Nonmetallic shaft

#### **Electrical Resistance Per Section:**

50.0 kilohms single section

#### Rotary Actuator Travel In Angular Deg:

7200.0

#### Center To Center Distance Between Center Terminal And Outside Terminal:

0.300 inches

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-250.0 to 250.0 single section

# NSN 5905-00-163-2008 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:

0.75 free air single section

## **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

# Actuator Travel Control Feature:

Clutch

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

## Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

#### Unit Of Measure:

--

# Demilitarization:

No

#### Fiig:

A002a0