NSN 5905-00-164-0824

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-164-0824 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.500 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.250 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.469 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **End Application:** Aircraft, prowler ea-6b & starlifter c-141; ticonderoga class cg (47), oliver perry class ffg, wasp class lhd; general purose electronic test equipment gpete **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 20.0 kilohms single section **Power Dissipation Rating Per Section In Watts:** 0.25 free air single section

3 tab, solder lug

-10.0/+10.0 single section

Terminal Type And Quantity:

Resistance Tolerance Per Section In Percent:

Shelf Life:

N/a

NSN 5905-00-164-0824

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A002a0