

View Online at <https://aerobasegroup.com/nsn/5905-00-164-1223>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.290 inches

Body Diameter:

0.750 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.935 inches

Mounting Bushing Length:

0.375 inches

Body Length:

0.980 inches

Overall Diameter:

0.750 inches

Undercut Diameter:

0.125 inches

Shaft Style:

Round, stepped

Actuator Type:

Single shaft

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.438 inches

Undercut Length:

0.430 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

25.0 kilohms all sections

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 2nd section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0