## NSN 5905-00-165-3124

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-165-3124 **Section Quantity:** 3 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.8750 inches Pilot Length: 0.0620 inches **Overall Length:** 2.4175 inches First Flat Length: 0.375 inches Flat Height: 0.235 inches **Undercut Diameter:** 1.875 inches **Undercut Width:** 0.0730 inches **Body Diameter:** 2.011 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.6875 inches **Body Length:** 1.730 inches **Mounting Lip Diameter:** 2.0000 inches **Mounting Lip Depth:** 0.0930 inches **Shaft Style:** Round, wedge flatted **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 

**Maximum Starting Torque:** 

3.20 inch-ounces

360.0

## NSN 5905-00-165-3124

**Maximum Running Torque:** 

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 3



3.20 inch-ounces
Shaft End Play:
0.00200 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.00100 inches
Shaft Radial Play:
0.002 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
80.0 kilohms all sections
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.25 to 0.25 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
275.0 all sections
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-200.0/+0.0 all sections
Power Dissipation Rating Per Section In Watts:
10.0 free air all sections
Function Conformity Per Section:
All sections absolute conformity
Fixed Tap Quantity Per Section:
2 1st section
Tap Location Tolerance Per Section:
-10.0 to 10.0 ohms 1st section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 all sections
Actuator Travel Control Feature:
Continuous motion
Tap Location From Ccw Terminal Per Section In Ohms:
20.0 1st section

25.0 all sections

**Function Characteristic Per Section:** 

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

2nd section 360 degrees sine

## NSN 5905-00-165-3124

Nonprecision Nonwire Wound Variable Resistor - Page 3 of 3



Terminal Type And Quantity:
14 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0