NSN 5905-00-165-3138

Film Fixed Resistor - Page 1 of 1

A001a0



View Online at https://aerobasegroup.com/nsn/5905-00-165-3138

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -100.0 to 100.0 Electrical Resistance: 91.000 kilohms Resistance Tolerance In Percent: -2.000 to 2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: -70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method:
Electrical Resistance: 91.000 kilohms Resistance Tolerance In Percent: -2.000 to 2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method:
P1.000 kilohms Resistance Tolerance In Percent: -2.000 to 2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: -70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method:
Resistance Tolerance In Percent: -2.000 to 2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: -70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method:
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method:
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method:
150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method:
-55.0 to 150.0 Inclosure Method:
Inclosure Method:
Encapsulated
Terminal Type:
Wire lead
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.010
Body Diameter:
0.138 inches
Body Length:
0.375 inches
Power Dissipation Rating In Watts:
0.500 free air
Style Designator:
Axial terminal each end
Test Data Document:
81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-r-39017/2 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig: