

View Online at <https://aerobasegroup.com/nsn/5905-00-166-0358>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.812 inches

Body Diameter:

1.812 inches

Shaft Diameter:

Between 0.2494 inches and 0.2497 inches

Shaft Length:

0.500 inches

Mounting Bushing Length:

0.312 inches

Body Length:

2.000 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Nonturn Device Location:

At 12 oclock

Nonturn Device Radius:

0.562 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Longitudinally positioned on the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

2.000 kilohms single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

Power Dissipation Rating Per Section In Watts:

5.0 free air single section

Fixed Tap Quantity Per Section:

32 single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Function Characteristic Per Section:

Single section table

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Test Data Document:

08440-463-1680 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

35 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0