Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-166-2981

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

1.8750 inches

Pilot Length:

0.0620 inches

Overall Length:

1.812 inches

Undercut Diameter:

1.87500 inches

Undercut Width:

0.0780 inches

Body Diameter:

2.000 inches

Angle Of Mounting Hole In Deg:

90.0

Angle Between Centerlines Of Mounting Holes In Deg:

120.0

Shaft Diameter:

0.125 inches

Shaft Length:

0.500 inches

Body Length:

1.062 inches

Mounting Lip Diameter:

2.0000 inches

Mounting Lip Depth:

0.0620 inches

Mounting Hole/stud Circle Diameter:

1.250 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Double ended shaft

Effective Electrical Rotation In Deg Angular Rotation:

340.0



Maximum Starting Torque:

0.50 inch-ounces

Maximum Stop Torque:

160.00 inch-ounces

Shaft End Play:

0.004 inches

Shaft Runout:

0.001 inches

Pilot Diameter Runout:

0.0015 inches

Shaft Radial Play:

0.001 inches

Screw Thread Diameter:

0.164 inches

Screw Thread Series Designator:

Unc

Screw Thready Qty Per Inch (tpi):

32.0

Mounting Facility Quantity:

3

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Threaded hole

Electrical Resistance Per Section:

5.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

350.0

Function Conformity Tolerance Per Section:

-0.20/+0.20 single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Power Dissipation Rating Per Section In Watts:

1.5 free air single section

Function Conformity Per Section:

Single section independent linearity

Fixed Tap Quantity Per Section:

1 single section

Tap Location Tolerance Per Section:

-2.0 to 2.0 ohms single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Stops



Tap Location From Ccw Terminal Per Section In Ohms:

2000.0 single section

Function Characteristic Per Section:

Single section linear

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Test Data Document:

86197-64112004 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

4 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0