NSN 5905-00-166-3047

Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-166-3047 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.8750 inches Pilot Length: 0.0620 inches **Overall Length:** 1.812 inches **Undercut Diameter:** 1.87500 inches **Undercut Width:** 0.0780 inches **Body Diameter:** 2.000 inches **Angle Of Mounting Hole In Deg:** 90.0 **Angle Between Centerlines Of Mounting Holes In Deg:** 120.0 **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.500 inches **Body Length:** 1.062 inches **Mounting Lip Diameter:** 2.0000 inches **Mounting Lip Depth:** 0.0620 inches **Mounting Hole/stud Circle Diameter:** 1.250 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Double ended shaft

Effective Electrical Rotation In Deg Angular Rotation:

340.0

NSN 5905-00-166-3047

Precision Nonwire Wound Variable Resistor - Page 2 of 3



Maximum Starting Torque:
0.50 inch-ounces
Maximum Stop Torque:
160.00 inch-ounces
Shaft End Play:
0.004 inches
Shaft Runout:
0.001 inches
Pilot Diameter Runout:
0.0015 inches
Shaft Radial Play:
0.001 inches
Screw Thread Diameter:
0.164 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
3
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Threaded hole
Electrical Resistance Per Section:
4.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
350.0
Function Conformity Tolerance Per Section:
-0.20 to 0.20 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
1.5 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-2.0/+2.0 ohms single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section

Stops

Actuator Travel Control Feature:

NSN 5905-00-166-3047

Precision Nonwire Wound Variable Resistor - Page 3 of 3



Tap Location From Ccw Terminal Per Sect	ion In Ohms:
---	--------------

2000.0 single section

Function Characteristic Per Section:

Single section linear

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Test Data Document:

86197-64112004 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

4 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0