NSN 5905-00-166-4443

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-166-4443

| 25.0/+25.0 Electrical Resistance: 38.300 kilohms Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Inclosure Method: Hermetically sealed Ferminal Type: Wire lead |
|--|
| Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead |
| Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead |
| Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Inclosure Method: Hermetically sealed Terminal Type: Nire lead |
| Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Inclosure Method: Idermetically sealed Terminal Type: Wire lead |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 nclosure Method: Hermetically sealed Terminal Type: Wire lead |
| Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 nclosure Method: Hermetically sealed Ferminal Type: Wire lead |
| 55.0 to 175.0 nclosure Method: Hermetically sealed Terminal Type: Wire lead |
| nclosure Method: Hermetically sealed Ferminal Type: Wire lead |
| Hermetically sealed Ferminal Type: Wire lead |
| Ferminal Type: Wire lead |
| Vire lead |
| |
| |
| Reliability Indicator: |
| Established |
| Reliability Failure Rate Level In Percent: |
| 0.001 |
| Body Diameter: |
| 0.250 inches |
| Body Length: |
| 0.750 inches |
| Power Dissipation Rating In Watts: |
| 0.500 free air |
| Style Designator: |
| Axial terminal each end |
| Test Data Document: |
| 31349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Shelf Life: |
| N/a |
| Jnit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| A001a0 |